



SAFETY DATA SHEET

Revision date 26-Sep-2019

Version 16

Supersedes Date: 19-Mar-2019

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name 2.1 VOC EUROSTAR KLEARCOAT

Product Code FS-6115.L05

UN/ID no UN1263

Recommended Use Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

5 STAR XTREME
a division of IAMG/International Autobody Marketing Group
1505 N. Hayden Road
Suite 111
Scottsdale, AZ 85257
www.5StarXtreme.com
1-87REFINISH

5 STAR XTREME
a division of IAMG/International Autobody Marketing Group
1368 United Blvd.
Unit 102
Coquitlam, BC V3K 6Y2
www.5StarXtreme.com
1-87REFINISH

E-mail address [No information available](#)

Emergency telephone number Chemtrec: 800-424-9300

Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Highly flammable liquid and vapor
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause respiratory irritation
May cause drowsiness or dizziness

PREVENTION

Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE

Get medical advice/attention if you feel unwell.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

OTHER HAZARDS

Not applicable.

UNKNOWN ACUTE TOXICITY

.0002% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	15 - 40 *
Acetone	67-64-1	7 - 13 *
n-Butyl acetate	123-86-4	5 - 10 *
Methyl acetate	79-20-9	5 - 10 *

Methyl n-amyl ketone	110-43-0	3 - 7 *
Ethylene glycol monobutyl ether acetate	112-07-2	0.5 - 1.5 *
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1 - 1 *

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact

If eye irritation persists: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Skin Contact

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower Wash contaminated clothing before reuse If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

Do NOT induce vomiting IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Flammable properties	Flammable liquid.
flash point	-4 °F / -20 °C
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Autoignition temperature	No information available
Explosion data	
Sensitivity to Mechanical Impact	No information available.
Sensitivity to Static Discharge	No information available.

Suitable extinguishing media

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe

fumes. May cause sensitization by skin contact.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

Section 7: HANDLING AND STORAGE

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	Alberta	British Columbia	Ontario TWA	Quebec	OSHA PEL
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³ F
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 750 ppm STEL: 1800 mg/m ³	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm STEL: 750 ppm	TWA: 500 ppm TWA: 1190 mg/m ³ STEL: 1000 ppm STEL: 2380 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m ³
n-Butyl acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 713 mg/m ³ STEL: 200 ppm	TWA: 20 ppm	TWA: 150 ppm STEL: 200 ppm	TWA: 150 ppm TWA: 713 mg/m ³ STEL: 200 ppm	TWA: 150 ppm TWA: 710 mg/m ³

		STEL: 950 mg/m ³			STEL: 950 mg/m ³	
Methyl acetate 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 606 mg/m ³ STEL: 250 ppm STEL: 757 mg/m ³	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm TWA: 606 mg/m ³ STEL: 250 ppm STEL: 757 mg/m ³	TWA: 200 ppm TWA: 610 mg/m ³
Methyl n-amyl ketone 110-43-0	TWA: 50 ppm	TWA: 50 ppm TWA: 233 mg/m ³	TWA: 50 ppm	TWA: 25 ppm TWA: 115 mg/m ³	TWA: 50 ppm TWA: 233 mg/m ³	TWA: 100 ppm TWA: 465 mg/m ³
Ethylene glycol monobutyl ether acetate 112-07-2	TWA: 20 ppm	TWA: 20 ppm TWA: 131 mg/m ³	TWA: 20 ppm	TWA: 20 ppm		

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Eye/face protection

Tight sealing safety goggles.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

Respiratory protection

In case of inadequate ventilation wear respiratory protection

Thermal Protection

No information available

Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid
Appearance	No information available
Odor	Solvent
Color	clear
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	56.05 °C / 133 °F
flash point	-20 °C / -4 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	8.93
specific gravity	1.07
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available

Kinematic viscosity No information available
Dynamic viscosity No information available

Other information

Section 10: STABILITY AND REACTIVITY

Stability Stable under normal conditions.
Incompatible materials Strong oxidizing agents.
Conditions to avoid Heat, flames and sparks.
Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2). Chlorine. Chlorine gas.
Possibility of Hazardous Reactions None under normal processing.
Hazardous polymerization None under normal processing.

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
 Causes serious eye irritation
Skin Contact
 May cause an allergic skin reaction
 Causes skin irritation
Ingestion
 Not applicable
Inhalation
 May cause respiratory irritation
 May cause drowsiness or dizziness

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Methyl acetate 79-20-9	> 5 g/kg (Rat)	> 5 g/kg (Rabbit)	= 16000 ppm (Rat) 4 h
Methyl n-amyl ketone 110-43-0	= 1600 mg/kg (Rat) = 1670 mg/kg (Rat)	= 12600 µL/kg (Rabbit) = 12.6 mL/kg (Rabbit)	2000 - 4000 ppm (Rat) 6 h
Ethylene glycol monobutyl ether acetate 112-07-2	= 2400 mg/kg (Rat)	= 1500 mg/kg (Rabbit)	> 400 ppm (Rat) 4 h
Bis(1,2,2,6,6-pentamethyl-4-piperidy l) sebacate 41556-26-7	= 2615 mg/kg (Rat)	-	-

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .
ATEmix (oral) 13127 Mg/kg
ATEmix (dermal) 100237 Mg/kg
ATEmix (inhalation-dust/mist) 30.6 mg/l
ATEmix (inhalation-vapor) 224 mg/l

UNKNOWN ACUTE TOXICITY .0002% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene glycol monobutyl ether acetate 112-07-2	A3			

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen.

Skin corrosion/irritation Causes skin irritation
Serious eye damage/eye irritation Causes serious eye irritation
Skin sensitization May cause an allergic skin reaction
Respiratory sensitization Not applicable
Germ cell mutagenicity Not applicable
Carcinogenicity Not applicable
Reproductive Toxicity Not applicable
Specific target organ toxicity (single exposure) May cause drowsiness or dizziness May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Not applicable
Aspiration hazard Not applicable

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity
 Environmental precautions Prevent product from entering drains.

Persistence and degradability
 No information available

Bioaccumulation
 No information available

Mobility
 No information available

Other adverse effects No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues/unused products Disposal should be in accordance with applicable regional, national and local laws and regulations

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal.

Section 14: TRANSPORT INFORMATION

UN/ID no	TDG	IMDG	IATA
UN1263	UN1263	UN1263	UN1263
Proper shipping name	Paint	Paint	Paint
Hazard Class	3	3	3
Packing Group	II	II	II
Environmental hazard			
Special Provisions		163, 367 EmS-No F-E, S-E	A3, A72, A192
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

DSL - Canadian Domestic Substances List

All components are listed or exempt from listing

Chemical Name	Canada - NPRI (National Pollutant Release Inventory)
Benzene, 1-chloro-4-(trifluoromethyl)-	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Acetone	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
n-Butyl acetate	Part 5, Individual Substances
Methyl acetate	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Methyl n-amyl ketone	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Ethylene glycol monobutyl ether acetate	Part 5, Other Groups and Mixtures

Section 16: OTHER INFORMATION

HMIS

Health hazards	2
Flammability	3
Physical hazards	0
Personal Protection	X

Prepared By Regulatory Department

Revision date 26-Sep-2019

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet